

BXW | WINDOW MODULE

The BXW is a $360^{\rm o}$ round LED fixture designed to uniformly illuminate architectural window frames, delivering a continuous halo of warm white light.

With a 3000K colour temperature and high-power LEDs, it creates subtle but powerful visual emphasis on building façades.

Housed in powder-coated aluminium and rated IP66, BXW is built for outdoor performance, offering a clean circular profile, simple surface mounting, and efficient 8W output. Ideal for buildings, architecture, and modern window accents.















5 YEAR IP66



PART NUMBER CONFIGURATOR

Prefix	LED Colour	Control	Beam Angle	Voltage	Housing	
BXW	RGBW	DMX	360 – 360°	24 – 24V DC	A – Aluminium	
	RGB					
	Dynamic White					
EXAMPLE: BXW – RGBW – X – 360 – 24 – A						

SPECIFICATIONS

Electrical	Power Consumption Operating Voltage Operating Temperature Storage Temperature	8W 24V DC -10°C TO 50°C - (14°F TO 122°F) -20°C TO 70°C - (-4°F TO 158°F)	
Physical	Dimensions Housing Weight/m IP Rating Source Life Control	119mm (D) x 175mm (H) Aluminium with powder coating 1Kgs IP66 50,000 hours under normal operating conditions Just On / Off	
Optical	Beam Angle 3 x 360° Colour Range RGBW, RGB, Dynamic White Connection 2-core DC input cable		
Control	Dimming Protocols	DMX	
Fixture Rating & Certifications	UL LISTED, CE RoHs COMPLIANT		
Limited Warranty 5 Years		Extendable warranty available	



BXW | WINDOW

DIMENSIONS & MOUNTING

DIMENSIONS OF LIGHT





