

## BXW | WINDOW MODULE

The BXW is a 360° round LED fixture designed to uniformly illuminate architectural window frames, delivering a continuous halo of warm white light.

With a 3000K colour temperature and high-power LEDs, it creates subtle but powerful visual emphasis on building façades.

Housed in powder-coated aluminium and rated IP66, BXW is built for outdoor performance, offering a clean circular profile, simple surface mounting, and efficient 8W output. Ideal for buildings, architecture, and modern window accents.



### PART NUMBER CONFIGURATOR

Prefix	LED Colour	Control	Beam Angle	Voltage	Housing
BXW	3000K	DMX	360 – 360°	24 – 24V DC	A – Aluminium
<b>EXAMPLE:</b> BXW – 3000K – X – 360 – 24 – A					

### SPECIFICATIONS

<b>Electrical</b>	<b>Power Consumption</b> <b>Operating Voltage</b> <b>Operating Temperature</b> <b>Storage Temperature</b>	8W 24V DC -10°C TO 50°C - (14°F TO 122°F) -20°C TO 70°C - (-4°F TO 158°F)
<b>Physical</b>	<b>Dimensions</b> <b>Housing</b> <b>Weight/m</b> <b>IP Rating</b> <b>Source Life</b> <b>Control</b>	119mm (D) x 175mm (H) Aluminium with powder coating 1Kgs IP66 50,000 hours under normal operating conditions Just On / Off
<b>Optical</b>	<b>Beam Angle</b> <b>Colour Range</b> <b>Connection</b>	3 x 360° 3000K 2-core DC input cable
<b>Control</b>	<b>Dimming Protocols</b>	DMX
<b>Fixture Rating &amp; Certifications</b>	<b>UL LISTED, CE</b> <b>RoHs COMPLIANT</b>	
<b>Limited Warranty</b>	<b>5 Years</b>	Extendable warranty available

### BXW | WINDOW

#### DIMENSIONS & MOUNTING

#### DIMENSIONS OF LIGHT

