

Bring any space to life with our premium RGBW Festoon Bulbs designed to provide vivid colour and all-weather performance. Each bulb delivers individually controllable dynamic lighting and smooth colour mixing, from warm whites to bold hues.

Engineered with a rugged IP67-rated housing and integrated catenary mounting system, these festoons are made to thrive outdoors, perfect for festivals, hospitality venues, and architectural accents. Easy to install, low-voltage, and long-lasting, they're the smart choice for standout, scalable illumination.





PART NUMBER CONFIGURATOR

Prefix	LED Colour	Control	Beam Angle	Power	Voltage	Mounting
FXF	RGBW	DMX RDM SPI	140 – 140º	1 – 1W	24 – 24V DC	HM – Hanging Mount AM – Awning Mount
EXAM						

SPECIFICATIONS

Electrical	Power Consumption	1W / unit		
	Operating Voltage	48V DC		
	Operating Temperature	-20°C TO 50°C - (-4°F TO 122°F)		
	Storage Temperature	-20°C TO 70°C - (-4°F TO 158°F)		
Physical	Dimensions	60mm (Dia) x 116mm (H)		
	Housing	PC housing with UV stabilizer		
	Connection	4-in-1 RGBW		
	IP Rating	IP67		
	Maximum Run Length	60 metres per string		
Optical	Beam Angle	140°		
	Colour Range	RGBW		
	LED Type	SMD LEDs		
Control	Dimming Protocols	DMX, RDM		
	Controlled	X-Stream with integrated SPI Booster		
Fixture Rating &	CE			
Certifications		CE		
Limited Warranty	5 Years	Extendable warranty available		





LED CTRL 1/483 BALMAIN ROAD LILYFIELD NSW 2040 AUSTRALIA SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. VISIT LEDCTRL.COM FOR THE MOST CURRENT SPECIFICATION.




FXF | FLEXIBLE FESTOON

DIMENSIONS







DATASHEET – SPECIFICATIONS



LED CTRL 1/483 BALMAIN ROAD LILYFIELD NSW 2040 AUSTRALIA SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. VISIT LEDCTRL.COM FOR THE MOST CURRENT SPECIFICATION.

LED Control PTE LTD UEN 201923077G ⓒ 2025 LEDCTRL. ALL RIGHTS RESERVED.