



## Colorimetric Parameters

Chromaticity Coordinate:  $x=0.2779$   $y=0.2929$   $u'=0.1866$   $v'=0.4424$

CCT=10043K(Duv=0.0041) Dominant WL:Ld =481.6nm Purity=22.3%

Peak WL:Lp=464.4nm FWHM=21.3nm

Render Index:Ra=40.3 Render Index:AvgR =33.7

R1 =18 R2 =56 R3 =74 R4 =35 R5 =39 R6 =48 R7 =53

R8 =0 R9 =0 R10=0 R11=21 R12=55 R13=25 R14=80 R15=3

## Photometric & Radiometric Parameters

Flux=263.7 lm Eff.:23.9 lm/W Fe=1.086 W

## Electrical parameters

V=24.00 V I=0.4597 A P=11.03 W PF=1.000 F=0.00 Hz

Status: Integral T = 313 ms Ip = 58317 (89%)

Test Mode: Fast Test; Sensitivity = High; Tecool: ON

Model:C-SFR-F21S-D24CC-56-RGBW(4000K)-5050-1M-RGB

Test By:SHAN

Temperature:25.3Deg

Manufacturer:

Assessor:

Date:2018-12-17 18:40:10

Humidity:63.0%

Remarks:

Standard: