

FXF

FLEXIBLE FESTOON SERIES

Bring any space to life with our premium RGBW Festoon Bulbs designed to provide vivid colour and all-weather performance. Each bulb delivers individually controllable dynamic lighting and smooth colour mixing, from warm whites to bold hues.

Engineered with a rugged IP67-rated housing and integrated catenart mounting systems, these festoons are made to thrive outdoors, perfect for festivals, hospitality venues, and architectural accents.

Easy to install, low-voltage, and long-lasting, they're the smart choice for standout, scalable illuminations.



X-Stream



IP 66



IK 07



5 YEAR WARRANTY



SPI



ANODISED ALUMINIUM



DMX



RGBW




PART NUMBER CONFIGURATOR

Prefix	LED Colour	Control	Beam Angle	Power	Voltage	Mounting
FXF	RGBW	D – DMX R – RDM S – SPI X – X-Stream	140 – 140°	1 – 1W	48 – 48V DC	HM – Hanging Mount AM – Awning Mount

Example: FXF -RGBW - D - 140 - 1 - 48 - HM

SPECIFICATIONS

Electrical	<div>Power Consumption</div> <div>Operating Voltage</div> <div>Operating Temperature</div> <div>Storage Temperature</div>	<div>1W / unite</div> <div>48V DC</div> <div>-20°C TO 50°C – (-4°F TO 122°F)</div> <div>-20°C TO 70°C – (-4°F TO 158°F)</div>
Physical	<div>Dimensions</div> <div>Housing / Lens</div> <div>Connection</div> <div>IP Rating</div> <div>Maximum Run Length</div>	<div>60mm (Dia) x 116mm (H)</div> <div>PC Housing with UV stabilizer</div> <div>4-in-1 RGBW</div> <div>IP67</div> <div>60 meters per string</div>
Optical	<div>Beam Angle</div> <div>Colour Range</div> <div>LED Type</div>	<div>140°</div> <div>RGBW</div> <div>SMD LEDs</div>
Dimming & Control	<div>Dimming Protocols</div> <div>Controlled</div>	<div>DMX, RDM</div> <div>X-Stream with integrated SPI Booster</div>
Fixture Rating & Certifications	CE	
Limited Warranty	5 Years	Extendable Warranty Available

FXF | FLEXIBLE FESTOON SERIES

DIMENSIONS & MOUNTING

