


## BXW | WINDOW LIGHT

The BXW is a 360° round LED fixture designed to uniformly illuminate architectural window frames, delivering a continuous halo of white or coloured light.

With well focused beam and high-power LEDs, it creates a subtle but powerful visual emphasis on building facades.

Housed in powder-coated aluminium and rated IP66, BXW is built for outdoor performance, offering a clean circular profile, simple surface mounting, and efficient 8W output. Ideal for buildings, architecture and modern window accents.



## PART NUMBER CONFIGURATOR

Prefix	LED Colour	White CCT	Control	Beam Angle	Voltage	Housing
BXW	RGBW RGB DW – Dynamic White (20K-50K) W – White (24K-60K)	24K – 2400K 27K – 2700K 30K – 3000K 35K – 3500K 40K – 4000K 50K – 5000K 60K – 6000K	D – DMX S – SPI X – XStream	360 – 360°	24 – 24V DC	A – Aluminium B – Black C – Custom RAL

Example: BXW – RGBW – 30K – D – 360 – 24 – A

## SPECIFICATIONS

Electrical	Power Consumption Operating Voltage Operating Temperature Storage Temperature	8W 24V DC -10°C TO 50°C -20°C TO 70°C
Physical	Dimensions Housing Weight IP Rating Source Life	119mm (D) x 175mm (H) Aluminium housing 1kgs IP66 50,000 hours under normal operating conditions
Optical	Beam Angle Colour Range Connection	360° RGBW, RGB, Dynamic White (2000K – 5000K), White ( 24000K – 6000K) 2-Core DC Input Cable
Dimming & Control	Dimming Protocols	DMX, SPI, X-Stream
Fixture Rating & Certifications	CE	
Limited Warranty	5 Years	Extendable Warranty Available

## BXW | WINDOW LIGHT

## DIMENSIONS AND MOUNTING

## DIMENSIONS OF LIGHT

